



ProCapture-T

➔ Fingerprint Access Control System

Fingerprint Capacity : 6,000
 Card Capacity : 10,000
 Transactions Capacity : 100,000
 User Photos : 3,000
 Event Photos : 7,000
 Communication : TCP/IP, RS485
 (For Slave Reader), USB Host, Wiegand
 Input / Output, Security Relay Box
 Hardware : 1.2GHz Dual Core CPU,
 Memory 128MB RAM / 256MB Flash,
 SilkID Fingerprint Sensor, 2,4 Inches
 TFT-LCD Touch Screen, 125KHz EM
 Reader / Mifare (Optional), Hi-Fi Voice &
 Indicator, Tamper Switch Alarm,
 Touch Keypad, 120° Wide Angle Camera
 Standard Functions : Access Levels / Groups /
 Holidays , DST / Bell Schedule, Duress Mode,
 Anti-Passback, Record Query, Custom
 Wallpaper & Screen Saver

Special Functions :

Multiple Verification Modes, Alive Finger Detection,
Event Snapshot, User Photo(Optional)

Access Control Interface :

Lock Relay Output, Alarm Output / Auxiliary Input,
Exit Button / Door Sensor, Doorbell Output

Compatibility : Wiegand Slave Reader, RS485

FP Slave Reader , BioSecurity Software

Working Temperature : -10 °C ~ 50 °C

Dimensions : 195.5 × 87 × 35 mm

Algorithm : Fingerprint Algorithm Finger v10.0

Power : Operating Voltage 12V DC,

Current Draw < 500 mA

Features

- Modern Design & Interactive UI
- Revolutionary SilkID Fingerprint Sensor
- Multiple Verification Modes: Fingerprint / Card / Password
- Outstanding Performance With Dry, Wet and Rough Fingers
- Built In Camera: Event Snapshot and User Photo (Optional)