



**eSSL-X5030C**

## Dual Energy X-ray Inspection System

### Specifications

Tunnel Size : W507mm × H305mm  
 Speed : 0.20 m/s  
 Height of Transmission Belt : 1000 mm  
 Maximum Load : ≤120 Kg (Adequate distribution)  
 Wire Resolution : 38 AWG (0.1mm metal wire)  
 Space Definition : Horizontal Φ1.0mm \ Vertical Φ2.0mm  
 Penetrate Definition : 32 AWG  
 Penetration : 32mm Steel board  
 Monitor : 17 inch LED  
 System Function : High density alarm, Explosive/Drug auxiliary detect, TIP, Luggage counter, System running timer, X-ray emitting timer, Training, 64 times continuous zoom in  
 Optional Function: Video surveillance system, Bidirection scan, Electrical weighing system, Energy saving mode, Ultrasonic rat repellent  
 Film Safety : ASA/ISO1600 standard of film safety

### X-ray System

Tube Voltage : 140 Kv  
 Cooling : Seal oil cooling/ 100%  
 Single Inspection Dosage Rate : ≤1.0 μ Gy  
 Radiation Leak Dosage : 0.1 μ Gy/h t(5cm from the shell)

### Install

Package Size (in mm): L1900 × W990 × H1320  
 Package Weight: 450 KG  
 Power Consumption: 1 kVA  
 Noise: 53.8 dB(A)

### Highlights

- Offer higher Wire Resolution with HAMAMATSU® X-ray detector
- True-color scanning image
- Widely usable for small parcels
- Excellent, ergonomic industrial design

### Standard

- Energy Saving Mode

### Optional

- Fingerprint Console Board
- Console Desk

### Dimensions

