



ET-1000A

ACCESSIBILITY



▶ ET-1000A: Heavy Duty Tripod Turnstile

Specifications

Passage width : 520mm
 Throughput rate : 30 p/m
 Power supply : 100 ~ 240V
 Operational voltage : 24V
 Max power consumption : 30 W
 Frequency : 50 ~ 60hz
 Protection level : IP54
 Working temperature : -25°C to +70°C
 Electro - magnetic drive : DC
 Dimension excluding bar (in mm) : (L)480 x (W)280 x (H)980
 Net weight including bar : 44kg

Features

Controller

- Semi-Auto mode
- Pure mechanical mode
- Single or Bi-directional function in mechanical and electrical versions
- Automatic reset of barrier arms after each passage
- Adjustable time out delay

Secondary Controller

- Fingerprint Capacity: 3,000
- RFID Capacity: 30,000

- Transaction Capacity: 1,00,000
- Integrated Controller: Inbio-260
- Relay: 12 V relay for lock
- Support Fire Alarm: Yes
- Protocol: RS485/Mifare/Proxy (optional)

Operating Mode

- Single passage in the set direction
- Bi-directional passage
- Free passage in the set direction
- Always free or locked

Materials

- Housing : SS304
- Barrier Arms : Stainless steel
- Lid (Optional) : Stainless steel or artificial stone (black / brown)

Dimensions

