eSSL®
Security at Fingertips

SpeedFace-H5

Face Fingerprint RFID Access

➤ High Speed Face Authentication System

Specifications

Capacity
User Capacity: 10,000
Face Capacity: 6,000
Fingerprint Capacity: 10,000
RFID Capacity: 10,000
Transaction Capacity: 2,00,000

Hardware
LCD: 5inch touch screen
CPU: Quad-core A17 1.8GHz
Memory: 2GB RAM / 16GB ROM
Camera: 2MP dual lens
Communication: TCP / IP, Wi-Fi (optional)
            RS232, RS485 for external reader
            Wiegand Input/Output
Access: Door lock, door sensor, alarm, exit button and auxiliary input
Audio: Loudspeaker

Operating
Voltage : 12V 3A
Temperature : -10°C ~ 45°C
Humidity : 10% ~ 90%

Features
• Enhanced Visible Light Facial Recognition with Deep Learning built-in
• 3-in-1 verification with Fingerprint, RFID and Facial Recognition
• 5-inch touch LCD
• Dual-camera for real-time face detection
• 6,000 face template capacity
• Recognition distance: 0.3 - 3 m
• Compatible with external RS232, RS485 and Wiegand reader
• TCP / IP, Wi-Fi communication

Accessories

RS485 Fingerprint Reader   RFID Reader   Exit Button

Electric Lock   Alarm   Sensor

Dimensions (mm)

134.93   21.50
166.93