

## FB-E-2216 Flap Barrier



### Specification

- Size (L\*W\*H) : 1400\*280\*980mm
- Pass width : 550mm
- Power : 50W
- Material : Top  $\delta=1.2\text{mm}$ / body  $\delta=0.9\text{mm}$  SUS304
- Bar Material : Acrylic Arm+RGB light
- Movement : Brushless Movement of Swing Gate
- Infrared sensor : 6 pairs
- Indicator Light : RGB light
- Drive Unit : Brushless DC 30K 40W
- Power Supply : 24V 150W
- Control Unit : Brushless control system
- Communication Interface : Dry contact & RS485
- Pass rate : 35-50 persons/minute
- Temperature :  $-20^{\circ}\sim+70^{\circ}$
- Humidity :  $\leq 90\%$  No condensation
- IP : IP4X
- Environment : Indoor and outdoor (outdoor with canopy)

## Functions & Features

- Reasonable and reliable design, low noise, smooth operation and long service life
- With functions of anti-tail, anti-reverse pass and so on
- Card can be set "with memory" or "without memory" functions
- With automatic reset function, i.e. after having access to the gate, the gate automatically restores to the locked state if not pass within the time set
- With infrared anti-clip function (anti-clip when gate is open or running)
- Compatible with IC, ID card, scanning and face recognition, etc.
- Two modes of operation are available: open or closed.
- Various working modes are available, including two-way card reading and one-way card reading, etc.

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.