

Elevator Control System



EC-10



EX-16

Specification

Elevator Controller - EC10

- ▶ Floor Button Control Relays : 10
- ▶ Fingerprint Capacity : 3,000
- ▶ Proximity Card Capacity : 30,000
- ▶ Event Capacity : 1,00,000
- ▶ Power Supply : 12V DC 1A
- ▶ Communication to computer : Ethernet, RS485
- ▶ Communication to EX16 : RS485
- ▶ Number of supported EX16 boards : 3


EX16

- ▶ Floor Button Control Relay :16
- ▶ Communication to EC10 : Rs485
- ▶ RS485 address : Set by DIP switch
- ▶ Power Supply : 12V DC 1A

Features:

- ▶ Supports both RFID and Fingerprint slave readers
- ▶ Fail Safe Mode
- ▶ Real-time upload of user access privileges
- ▶ Real-time event monitoring
- ▶ User-defined floor access privilege
- ▶ Software :- Bio Security 3.0.1.0_R
- ▶ Database Type :- PG SQL / MS SQL / Oracle

Connectivity Diagram



Disclaimer: Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase.

Actual product may differ slightly to that depicted for ongoing product development

www.esslsecurity.com