



Aiface Arion

Display	5-Inch
Camera	WDR Low Light Camera @ 2MP
Operation System	Linux
Hardware	CPU: 1.GHz Dual Core RAM: 1GB ROM: 8GB
Authentication Method	Face / Fingerprint / Card / Password (Virtual Keypad)
Fingerprint Template Capacity	6,000 (1:N)
Face Template Capacity	6,000 (1:N)
Card Capacity	10,000 (1:N)
Transaction Capacity	200,000 (1:N)
Biometric Verification Speed	Fingerprint: < 0.3 sec Facial Recognition: < 1 sec
Touchless Biometric Recognitio	1cm to 100cm - Facial Recognition

False Acceptance Rate (FAR) %	Facial Recognition: FAR ≤ 0.01% Fingerprint: FAR ≤ 0.0001%
False Rejection Rate (FRR) %	Facial Recognition: FRR ≤ 0.02% Fingerprint: FRR ≤ 0.01%
Card Type	Proximity ID Card@125 kHz Mifare IC Card@13.56 MHz (Optional) HID Prox, HID Iclass (Optional)
Communication	TCP/IP, Wiegand (Input & Output), RS485,Wi-Fi
Access Control Interface	Electro Magnetic Lock/ Electric Lock, Door Sensor, Exit Button, Alarm Output
Power Supply	DC 12V 3A
Operating Temperature	-10°C to 45°C
Operating Humidity	10% to 90% RH (Non-condensing)
Dimensions	91.93mm * 202.93mm * 21.5mm (L*W*H)
Supported Software	eTimetracklite

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.
www.esslsecurity.com