



Aiface Pluto-New

- Display : 4.3"@ TFT Color Touch LED Screen (272*480)
- Camera : WDR Binocular Camera @ 1MP
- Operation System : Linux
- **Hardware** CPU : Dual Core@1GHz
RAM : 512MB
ROM : 8GB
- Authentication method : Face / Card / Password (Virtual Keypad)
- Face Template Capacity : 1,500 (1:N)
- Card Capacity : 1,500 (1:N)
- User Capacity : 1,500 (1:N)
- Transaction Capacity : 1,50,000 (1:N)
- Max. User Password Length : 8 Digits
- Biometric Authentication Speed : less than 0.35 sec (Facial Authentication)
- Touchless Biometric Authentication Distance : 30cm to 200cm (Facial Authentication)
- False Acceptance Rate (FAR) % : $FAR \leq 0.01\%$ (Visible Light Facial Authentication)
- False Rejection Rate (FRR) % : $FRR \leq 0.02\%$ (Visible Light Facial Authentication)
- Card Type : Proximity - ID Card @125 kHz (Standard)
- Communication : TCP/IP*1, Wi-Fi, Wiegand (Input or Output)*1, RS485*1, USB: Type A (USB Drive Only)*1, Aux Inputs *1, Electric Lock*1, Door Sensor*1, Exit Button*1, 12V Output*1
- Access Control Interface : Electro Magnetic Lock/ Electric Lock, Door Sensor, Exit Button, Alarm Output
- Power Supply : DC 12V 3A
- Operating Temperature : -5°C to 45°C
- Operating Humidity : 10% to 90% RH (Non-condensing)
- Dimensions : 175.00 mm * 84.50 mm * 21.65 mm (L*W*H)
- Supported Software : eTimetracklite
- Installation : Wall-mount

- **Features:**

- Visible Light Facial Authentication Technology
- Multiple Authentication Methods: Facial / RFID / Password
- Available RFID Modules: 125 kHz ID Card
- User Data Synchronization: User data can be downloaded/uploaded from one device to another via a USB drive
- Advanced access control functions (Wiegand input or output shared; RS485 communication; Electric Lock; Door Sensor; Exit Button)

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

www.esslsecurity.com

ISO **FC** **CE** **ROHS**