

Multi-Biometric Time Attendance & Access Control System

MB160





Specification

Storage Capacity

Face Capacity: 1,500
Fingerprint Capacity: 2,000
ID card Capacity: 2,000
Transaction Capacity: 1,00,000

Visua

Display: 2.8-inch TFT Screen

Communication

Communication: TCP/IP, USB-Host

Push Data : Yes GPRS : Optional

Standard Functions

SMS, DLST, Scheduled-bell, Self-Service Query, Automatic Status Switch, T9 Input, Photo ID, Camera, Multi-verification

Interface for Access Control

3rd Party Electric Lock, Door Sensor, Exit Button, Alarm

Optional Function

ID , Work Code, RS232 Printer

Power & Environment

Battery : (Optional)

Power Supply : DC 12V --- 1.5A Verifcation Speed : ≤0.5 Sec Operating Temperature : 0°C - 45°C

Dimension (in mm): (L)167.5 x (W)148.8 x (H)32.2

Features

- High verification speed
- Professional firmware and platform make it more flexible
- Intuitive and stunning UI design
- Sophisticated and lightweight design, fits in any environment

Disclaimer: Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase.

Actual product may differ slightly to that depicted for ongoing product development

www.esslsecurity.com