



# FE-1

## RFID Encoder and Updater

### Technical Specifications :

- Power Supply: DC5V +-10%
- Current Consumption: 75mA
- Reading Distance: 0-50mm
- Card Operation Frequency: 13.56MHZ
- Indicator (LED/Beeper): Power /Communication /Good

### Features :

- Compatible card type: Mifare Classic 1K, Mifare Classic 4K, CUP card.
- Card Standard: ISO1443 A&B read/Write.
- Communication: USB, Standalone type.
- Driver: No additional driver needed, Compatible with windows 7, 8, 10, 11.

### Physical Characteristics :

- Dimensions: 127(L)\*87(W)\*39(H) mm
- Color: Black

### Operating Conditions :

- Temperature:-20-60C
- Storage:-20-60C

### Built -in-Peripherals :

- LED: 2 single -color: Red and Green
- Buzzer: Monotone

### USB Host Interface :

- Connector Type: Standard Type A
- Power Source: From USB port
- Supply current: 5V
- Protocol: USB HID Keyboard Class

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.  
[www.esslsecurity.com](http://www.esslsecurity.com)