

Standalone RFID Time Attendance & Access Control System

S-990A



Specification

Card Capacity : 30,000
Transaction Storage : 1,00,000
Card Reader : Yes
Push data : Standard
CPU : 32 bit Microprocessor - 800Mhz
FAR : <=0.0001% / FRR : <=1%
Identification Speed : <=0.1 sec
Algorithm Ver : NA
Display : 2.8" TFT
Keypad : 4 x 4 with 5 function Keys
Schedule Bell/Speaker : Mini Speaker
Communication : RS232/485, TCP/IP
Standard Features : work code, SMS, DLST,
Self service query, Status Switch
Power Supply : 12V DC , 1.5Amp
Operating Temperature : 0°C to 45°C
Operating Humidity : 20% -80%
Dimension : 210 x 157 x 40mm
Access Control : Wiegand : In & Out
both 26 or 34 bit (With or without site code)

Relay : 12 V relay for lock EM lock,
Bolt Lock or Strike lock
Support Fire Alarm : Yes / Door Sensor ; Yes
Anti Passback : Yes / Door Bell : Yes
Support exit reader : KR500E / Exit Button, 101HE
Battery : Yes / Card Readers : Yes
Communication : GPRS, Wifi (Optional)
Printer : Optional

Compatibility :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)

Compatible Software & SDK :

- Etime track lite desktop & web
- SDK for desktop applications
- Web based Device Manager/ePush server using Push data. Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications